

Product Information

IBS Exhaust System MA

Issue 12/2012

Art.-No.2120013

Field of Application

IBS exhaust systems are mandatory for technical ventilation according to BGR 180 (ZH 1/562) if solvents are used with a flashing point between 40°C and 55°C, in case of the IBS special cleaning agent Quick, for example. The exhaust fan blows possibly developing aerosols outwards.

Safety

The device complies with the requirements of the European Machine Directive and carries the CE mark.

Advantages

- **Easy assembly** – simply attach to parts cleaning device
- **Long service life** – robust, stable industrial design
- **Construction** – sturdy steel plate, welded construction, coated
- **Workplace-friendly** – hinged cover

Electrical Equipment:

Electrical connected load:	0.14 kW
Voltage:	230 V - 50 Hz
Electrical motor, protection class:	IP 54
Insulation class:	B

Technical Data:

Air flow:	540 cbm / h
Static pressure:	430 Pa
RPM:	2550 rpm
Max. environmental temperature:	40°C

Dimensions:

Dimensions (L x W x H):	1140 x 660 x 280 mm
Weight:	45 kg

IBS Scherer GmbH
Gewerbegebiet
55599 Gau-Bickelheim
Germany

Phone +49-6701-9383-0
Fax +49-6701-9383-33
Web www.ibs-scherer.eu
Email info@ibs-scherer.de

General Manager:
Axel Scherer, Dipl.-Eng.
Registergericht Mainz
HRB 32454

