AC-9002	**Light Mineral Filler**
	Color: Gray Density: 0.60-0.85 g/cm³ Bulk density: 0.35 – 0.4 g/cm³ Can be used with Epoxy and Polyurethane Systems Packaging: 20 kg

AC-9004	**Inorganic Filler**
	Color: White Density: 2.4 g/cm³ Bulk density: 1.6 g/cm³ Can be used with Epoxy and Polyurethane Systems Packaging: 20 kg, 1000 kg

AC-9102	**Paste Release Agent**
	Wax based release agent for general applications. Can be polished. Color: White Density: 0.8 g/cm³ Packaging: 12x1 kg

AC-9103	**Liquid Release Agent**
	Wax based liquid release agent for the release of general and detailed mold surfaces. Can be polished. Color: White Density: 0.72 g/cm³ Packaging: 6x0.75 kg, 4x3.75 kg

Storage

Original containers should be kept tightly sealed and stored at ambient temperatures (15°C to 30°C) in a dry place. If properly stored the products have the shelf-life indicated on the product label.
Partly used containers should always be sealed appropriately and used up as soon as possible.

Handling Precautions

Good workplace ventilation is to be ensured during processing. At the same time, the employer's liability insurance association's industrial hygiene safety regulations regarding the handling of reaction resins and their hardeners are to be observed. Please take heed of the appropriate safety data sheets.

RAMPF Tooling Solutions GmbH & Co. KG
Robert-Bosch-Str. 8-10 | D-72661 Grafenberg
T +49.71 23. 93 42-1600
F +49.71 23. 93 42-1666
E tooling.solutions@rampf-gruppe.de
www.rampf-gruppe.de

Our recommendations on the use of the material are based on many years of experience and current scientific and practical knowledge. They are, however, provided without any obligation on our part and do not relieve the buyer of the need for suitability tests. They do not constitute a legal relationship, nor are any protected third party rights whatsoever affected thereby.